

Backer Plate - Japanese Millet

John Deere Sprocket Transmission

Bulk Fill tank settings: 8-10 (inches of water)

Average seeding rate for small grains planted with the SeedRight BackerPlate and Kinze Brush Type Meter

Transmission		Rates (lbs/acre) & Row Spacing							
Sprockets		High Range			Low Range				
Drive	Driven	30	20	15	30	20	15		
35	24	7.8	11.6	15.5	2.9	4.4	5.8		
35	25	7.4	11.2	14.9	2.8	4.2	5.6		
35	26	7.2	10.7	14.3	2.7	4.0	5.4		
35	27	6.9	10.3	13.8	2.6	3.9	5.2		
35	28	6.7	10.0	13.3	2.5	3.7	5.0		
29	24	6.4	9.6	12.9	2.4	3.6	4.8		
29	25	6.2	9.3	12.3	2.3	3.5	4.6		
29	26	5.9	8.9	11.9	2.2	3.3	4.5		
29	27	5.7	8.6	11.4	2.1	3.2	4.3		
29	28	5.5	8.3	11.0	2.1	3.1	4.1		
24	24	5.3	8.0	10.6	2.0	3.0	4.0		
24	25	5.1	7.7	10.2	1.9	2.9	3.8		
24	26	4.9	7.4	9.8	1.8	2.8	3.7		

Transmission Sprockets		Rates (lbs/acre) & Row Spacing							
		High Range			Low Range				
Drive	Driven	30	20	15	30	20	15		
24	27	4.7	7.1	9.5	1.8	2.7	3.5		
24	28	4.6	6.8	9.1	1.7	2.6	3.4		
20	24	4.4	6.7	8.9	1.7	2.5	3.3		
20	25	4.3	6.4	8.5	1.6	2.4	3.2		
20	26	4.1	6.1	8.2	1.5	2.3	3.1		
20	27	3.9	5.9	7.9	1.5	2.2	3.0		
20	28	3.8	5.7	7.6	1.4	2.1	2.9		
16	24	3.4	5.1	6.8	1.3	2.0	2.7		
16	25	3.4	5.1	6.8	1.3	1.9	2.6		
16	26	3.3	4.9	6.5	1.2	1.8	2.5		
16	27	3.2	4.7	6.3	1.2	1.8	2.4		
16	28	3.0	4.6	6.1	1.1	1.7	2.3		

Cells Per Disc: 30 Cell Milo

Note: Seeding rates are approximations, environmental conditions can affect planting rates; Always field check populations.



Phone: 260-245-5006 Email: info@davaus.com Website: Davaus.com